CLAIMS:

5

- 1. A method for analyzing of speech, the method comprising the steps of:
 - inputting of a speech signal,
 - obtaining of the first harmonic of the speech signal,
 - determining of the phase-difference ($\Delta \phi$) between the speech signal and the first harmonic.
- 2. The method of claim 1, the determination of the phase difference comprising the steps of:
 - determining the location of a maximum of the speech signal,
- determining the phase difference between the maximum and phase zero of the first harmonic of the speech signal.
 - 3. The method of claims 1 or 2, whereby the speech signal is a diphone signal.
- 15 4. A method for synthesizing speech, the method comprising the steps of:
 - selecting of windowed diphone samples, the diphone samples being windowed by a window function being centered with respect to a phase angle which is determined by a phase difference between a speech signal and the first harmonic of the speech signal,
- 20 concatenating the selected windowed diphone samples.
 - 5. The method of claim 4, the speech signal being a diphone signal.
- 6. The method of claims 4 or 5, the window function being a raised cosine or a triangular window.
 - 7. The method of anyone of claims 4, 5 or 6 further comprising inputting of information being indicative of diphones and a pitch contour, the information forming the basis for selecting of the windowed diphone samples.

14

WO 03/090205 PCT/IB03/01249

- 8. The method of anyone of the preceding claims 4 to 7, whereby the information is provided from a language processing module of a text-to-speech system.
- 5 9. The method of anyone of the preceding claims 4 to 8 further comprising:
 - inputting of speech,
 - windowing the speech by means of the window function to obtain the windowed diphone samples.
- 10 10. A computer program product for performing a method in accordance with anyone of the preceding claims 1 to 9.
 - 11. A speech analysis device comprising:
 - means for inputting of a speech signal,
- 15 means for obtaining the first harmonic of the speech signal,
 - means for determining the phase difference ($\Delta \phi$) between the speech signal and the first harmonic.
- The speech analysis device of claim 11, the means for determining the phase
 difference being adapted to determine a maximum of the speech signal and to determine a
 phase zero (φ₀) of the speech signal in order to determine the phase difference between the
 maximum of the speech signal and the phase zero.
- 13. The speech analysis device of claims 11 or 12, wherein the speech signal is a25 diphone signal.
 - 14. A speech synthesis device comprising:

30

- means for selecting of windowed diphone samples, the diphone samples being windowed by a window function being centered with respect to a phase angle which is determined by a phase difference between a speech signal and the first harmonic of the speech signal,
- means for concatenating the selected windowed diphone signals.

WO 03/090205

10

30

15

PCT/IB03/01249

- 15. The speech synthesis device of claim 14, wherein the speech signal is a diphone signal.
- 16. The speech synthesis device of claims 14 or 15 the window function being araised cosine or a triangular window.
 - 17. The speech synthesis device of anyone of the claims 14, 15 or 16 further comprising means for inputting of information being indicative of diphones and a pitch contour, the means for selecting the windowed diphones being adapted to perform the selection based on the information.
 - 18. A text-to-speech system comprising:
 - language processing means for providing of information being indicative of diphones and a pitch contour,
- speech synthesis means comprising means for selecting of windowed diphone samples based on the information, the diphone samples being windowed by a window function being centered with respect to a phase angle which is determined by a phase difference between a speech signal and a first harmonic of the speech signal and means for concatenating the selected windowed
 diphone samples.
 - 19. The text-to-speech system of claim 18, whereby the window function is a raised cosine or a triangular window.
- 25 20. A speech processing system comprising:
 - means for inputting of a signal comprising natural speech signal,
 - means for windowing the natural speech signal by means of a window function being centered with respect to a phase angle which is determined by a phase difference between a speech signal and the first harmonic of the speech signal to provide windowed diphone samples,
 - means for processing of the windowed diphone samples,
 - means for concatenating the selected windowed diphone samples.